


铁氟龙软管 PTFE Hose



内层 Inner Tube:铁氟龙 PTFE
 外层Cover:A Sigle Braid OF Stainless Steel
 温度范围 Temperature Range:-54℃~+204℃
 注：双层编织可提供更高的性能。

软管代码	软管内径	软管外径	最大工作压力	最低爆破压力	最小弯曲半径
HOSE PART NO	HOSE I. D	HOSE O. D	MAX W. P	MIN BURET PRESSURE	MIN BEND RAD
	mm	mm	Mpa	Mpa	mm
PH179-03	5.1	7.6	21.0	84.0	50
PH179-04	6.3	9.7	21.0	84.0	75
PH179-05	8.0	11.2	17.5	70.0	100
PH179-06	9.6	12.6	16.5	66.0	170
PH179-08	12.8	16.5	12.0	48.0	165
PH179-10	16.0	19.8	8.8	35.2	200
PH179-12	19.1	22.8	7.5	30.0	230
PH179-16	25.4	29.5	6.2	24.8	305



软管代码	软管内径	软管外径	最大工作压力	最低爆破压力	最小弯曲半径
HOSE PART NO	HOSE I. D	HOSE O. D	MAX W. P	MIN BURET PRESSURE	MIN BEND RAD
	mm	mm	Mpa	Mpa	mm
PH382-04	6.4	11.9	36.5	109.5	40
PH382-05	8.0	13.7	31.5	94.5	45
PH382-06	9.5	14.7	30.0	90.0	65
PH382-08	12.7	18.5	26.5	79.5	75
PH382-10	16.0	22.4	23.5	70.5	115
PH382-12	19.1	26.2	20.0	60.0	240
PH382-16	25.4	32.0	15.0	45.0	320